



POWERFUL PERFORMANCE, ENHANCED OPERABILITY, ENERGY EFFICIENT

Groundbreaking, full-color ledger-size document systems.

Sharp's new MX-4110N/4111N/5110N/5111N Color Series document systems combine the simplicity of touch-screen menu navigation with robust multi-tasking workflow features that can elevate your office productivity to new levels. A large 10.1" (diagonally measured) high-resolution tilting, touch-screen display offers groundbreaking real-time image preview with intuitive flick and tap editing to help ensure your documents are produced accurately and without waste. The new MX Color Series also offers many advanced features such as a fully customizable home screen, dynamic action menus that provide feature-specific guidance, and an available full-size retractable keyboard for easy data entry. Plus, with Sharp's enhanced second-generation micro-fine toner technology and true 1200 x 1200 dpi print resolution, the new MX Color Series can help your business produce professional looking color documents in-house with breathtaking image quality that is also economical. The new MX-4110N/4111N/5110N/5111N Color Series has been built on the latest Sharp OSA® Development Platform, making integration with network applications and cloud services easier than ever. And, with Sharp's Industry leading security platform with standard 256 bit data encryption and overwrite protection, you can rest assured that your intellectual property is well protected.



Drag and drop touch control for intuitive operation!



Advanced features plus multi-functional capability allow you to meet tomorrow's document needs today.



- Large 10.1" high resolution touch-screen display with tilt view
- Real-time image preview feature with flick, tap and slide menu navigation
- Fully customizable home screen feature enables users to add custom backgrounds and custom icons, change the display language and more

- Action menus provide users with feature-specific guidance
- Quickly scan both sides of a document at once with the standard 150-sheet duplex single pass feeder (DSPF) on the MX-4111N and MX-5111N; a 100-sheet reversing single pass feeder (RSPF) is standard on the MX-4110N and MX-5110N
- Full-size, retractable keyboard allows quick, easy and accurate data entry (standard on the MX-4111N/5111N)
- Web browser feature on the MX-5111N allows easy access to web-based information
- 1200 x 1200 dpi printing provides clear, crisp images even on jobs with fine detail
- Industry leading ImageSEND[™] function scans documents to USB devices, network folders, e-mail and more
- Scans documents at up to 75 images per minute (MX-4111N/5111N) in both Black and Color

- Network ready PCL[®] 6/Postscript[®] 3[™] printing system with direct print function and available XPS option
- Robust 86 GB document filing system with thumbnail view and image preview features for easy identification
- Supports the latest Sharp OSA® Development Platform, enabling businesses to easily integrate with network applications and cloud services
- Supports Sharp's award-winning security platform with standard 256 bit data encryption and up to 7 times overwrite protection
- Energy efficient belt fusing system offers low power consumption, fast warm up and enhanced print quality

Innovation & Navigation

MX-4110N/4111N/5110N/5111N SPECIFICATIONS

Main Specification	s	Network Printing	System	Saddle Stitch Fini	isher (MX-FN10: option)
MX-4110N/4111N	Base models include multitasking controller, 100 sheet RSPF	PDL	Standard PCL® 6/PCL5c compatible, PostScript® 3™ compatible,	Туре	Console finisher with dual exit trays (mounts on left side
	(MX-4110N/5110)/150 sheet DSPF (MX-4111N/5111N), PCL6/5c/	Decelutio -	optional XPS	Output Torres	of host machine)
	PS3 network printing/scanning, auto duplexing, 2 x 500-sheet paper drawers, 100-sheet bypass tray. Developer is included.	Resolution Print Speed	1200 x 1200 dpi 41/51 pages per minute (8½" x 11")	Output Trays	Upper tray: Offset stack tray Lower tray: Book tray for saddle stitch
	Desktop, color multi-function digital document system	Print Drivers	Windows 2000, Windows Server® 2003-2008, Windows XP, Windows	Output Capacity	1000 sheets (letter/statement size) or 500 sheets (legal, ledger, letter)
Display	10.1" (diagonally measured) color dot matrix high-resolution touch	1111112 5111010	XP x64, Windows Server x64, Windows Vista®, Windows Vista® x64,	Stapling	Up to 50 sheets (letter/statement) or 25 sheets (legal, ledger or mixed
., .,	panel tilting display. 1024 x 600 dots (W-SVGA)		Windows 7, MAC OS®, 9.2.2, OSX (including 10.2.8, 10.3.9,	Output Delivery	Face down
Functions	Copy, print, network print, network scan, document filing and fax1		10.4.11, 10.5-10.5.8, 10.6-10.6.1), all MAC PPD.	Stapling Media	Plain paper, letter/legal/ledger size or mixed
	Dry electrostatic transfer/Dual component developer/Magnetic	Features	Auto configuration, continuous printing, electronic sorting, offset	Stapling Positions	1 front, 1 rear, or both
	brush development/OPC drums/Belt type fusing/white LED exposure		stacking, N-up printing, duplex printing, transparency inserts, margin	Saddle Stitch	Center stitch/center folding (2 staples) letter/legal/ledger
Originals Max Original Size	Sheets and bound documents 11" x 17"		shift, image rotation, different cover page, poster print, job bypass print, job retention, confidential print, proof print, user authentication,	Function Saddle Stitch	paper sizes Up to 10 sets (11-15 sheets per set)/15 sets (6-10 sheets per set)/
	Min. 5½" x 8½". Max. 11" x 17" + 12" x 18"		image stamp and watermarks. Additional features: Multiple pamphlet,	Max. Sets	20 sets (1-5 sheets per set)
1. 2	41/51 ppm B&W/Color (8½" x 11")		network tandem print, carbon copy print mode, different cover	Power Cons.	70 W or less (MX-FN10)/138 W or less (MX-FN18)
Multiple Copy	Max. 999 copies		page/last page/other page, form overlay, tab paper settings, tab	Hole Punching	Optional three-hole punch unit MX-PNX5B
First Copy Time	MX-4110N MX-4111N MX-5110N MX-5111N		printing, chapter inserts, page Interleave and bar code font printing ¹		(MX-FN10)/MX-PNX6B (MX-FN18)
(Seconds) ²	Black Color Black Color Black Color Black Color	Direct Printing	File Types: TIFF, JPEG, PCL, PRN, TXT, PDF, Encrypted PDF, PostScript	Weight	Approx.: 88½ lbs. (MX-FN10)/Approx.: 161 lbs. (MX-FN18)
	Platen Glass 4.7 6.7 4.7 6.7 4.1 5.7 4.1 5.7		and (optional) XPS1 Methods: FTP, Web page, E-mail and USB memory	Dimensions	26" (w) x 25" (d) x 39" (h) (MX-FN10 with tray extended)
	Doc. Feeder 7.7 9.8 7.4 10.3 7.0 8.8 6.7 9.2	Resident Fonts	80 outline fonts (PCL), 136 fonts (PS)	AV OLIGINATION PROTE	has (MV PMA and Park)
	34 seconds or less ²	Interface	RJ-45 Ethernet 10/100/1000 Base-T, USB 2.0		her (MX-FN11: option)
_	25% to 400% in 1% increments (with document feeder 25%-200%) MX-4110/5110N: 100-sheet RSPF/MX-4111N/5111N: 150-sheet DSPF	Operating Systems	Windows Server 2003-2008, Windows 2000/XP, Windows Vista, Windows 7, MAC OS 9-9.2.2, MAC OSX 10.2.8, 10.3.9, 10.4.11,	Туре	Console stacking finisher with dual exit trays (mounts on left side of host machine)
	RSPF Copy/Scan: Up to 51 IPM2 2	Oyoteilio	10.5-10.5.8, 10.6-10.6.5, Novell® Netware® 3x, 4x, 5x, Sun® OS	Output Trays	Fixed position upper tray and offset stacking lower tray
	DSPF Copy: Up to 75 IPM (B&W)/51 IPM (Color);		4.1x, Solaris® 2x, Unix®, Linux® and Citrix® (Metaframe,	Output Trays	Upper tray: 1,550 sheets (letter size, non-stapled)
	DSPF Scan: Up to 75 IPM ²		Presentation Server 4, 4.5) and Windows Terminal Services. ¹	output outputity	Lower tray: 2,450 sheets (letter size, non-stapled)
	5½" x 8½", 8½" x 11", 8½" x 11" R, 8½" x 14", 11" x 17"	Network	TCP/IP (IPv4, IPv6, IPSEC) SSL (HTTP, IPP, FTP), SNMPv3, SMTP,	Stapling	Three position; Up to 50 sheets (letter/statement)
	Standard: (2) 500-sheet paper drawer (letter/legal/ledger/statement	Protocols	POP3, LDAP, 802.1x for Windows and Unix. LPD and LPR for Unix.	Power Consumptio	
System	size) and 100-sheet bypass tray (letter/legal/ledger/statement/envelope		IPX/SPX® for Novell environments. EtherTalk® and NetBEUI. AppleTalk®	Hole Punching	Optional three-hole punch unit MX-PNX6B
	size). Optional: Single or double drawer paper deck (500 or 1000		for Macintosh® environments.1	Weight Approx	97 lbs.
	sheets), letter/legal/ledger/statement size.	Printing	LPR, IPP, IPPS, PAP, Raw TCP (port 9100), FTP and Novell	Dimensions	20½" (w) x 25½" (d) x 43½" (h) (MX-FN11 with tray extended)
	Paper drawers: 16 lb. bond -110 lb. index. Other paper types include	Protocols	Pserver/Rprinter		
	plain, pre-printed, recycled, pre-punched, letterhead and color paper.	Network	IP/MAC address filtering, protocol filtering, port management, user	Optional Equipme	
	Bypass Tray: 16-28 lb. bond (plain paper), 13-16 lb. bond (thin paper), 110-140 lb. index (heavy paper), 20-24 lb. bond (Monarch/Com-10	Security Standards	authentication and document administration.¹ IEEE-2600™-2008, DoD (NSTISSP) #11, DoD Directive 8500.2,	MX-DE15 MX-DE16	Stand/1 x 500 Sheet Paper Drawer Stand/2 x 500 Sheet Paper Drawer
	envelope), tab paper (letter). Also label paper, gloss paper, pre-printed,	Security Standards	DoD (DISA) ¹	MX-51ABD	Rolling Cabinet Base
	recycled, pre-punched, letterhead, color paper and OHP film.		505 (510)	MX-LC11	Large Capacity Tray (requires MX-DE15 or MX-DE16)
Duplexing	Standard automatic duplex copying and printing	Network Scanning	System	MX-FNX9	Inner Finisher
	Up to 1250 MHz Multi-Processor Design	Scan Modes	Standard: Color, monochrome, grayscale	MX-PNX1B	3 Hole Punch Unit (requires MX-FNX9)
Interface	RJ-45 Ethernet (10/100/1000Base-T), USB 2.0 (2 host ports, front	Max Original Size	11" x 17"	MX-FN10	1K Saddle Stitch Finisher
	and rear), USB 2.0 (1 device port, rear)	Optical Resolution	600 dpi	MX-PNX5B	3 Hole Punch Unit (requires MX-FN10)
	Standard 2 GB Copy/Scan; 1 GB Printer Memory	Output Modes	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi	MX-FN11	4K Stacking Finisher
	160 GB; 86 GB for document filing	Image Formats	Monochrome: TIFF, PDF, Encrypted PDF, XPS	MX-FN18	4K Saddle Stitch Finisher
Copy Resolution Color Modes	Scan: B&W/color: 600 x 600 dpi; Copy Output: B&W/color: 600 x 600 dpi Auto Color Control (ACS), Full Color Mode, Monochrome (B/W)		Color: Grayscale, Color TIFF, JPEG, PDF, Encrypted PDF, XPS Internet Fax: TIFF-FX, FIFF-F, TIFF-S ¹	MX-RB11 MX-PNX6B	Paper Pass Unit (requires MX-FN10/11/18) 3 Hole Punch Unit (requires MX-FN11/18)
Exposure	Modes: Automatic Text, Text/Photo, Text/Printed-Photo, Printed-Photo,	Image	Monochrome Scanning: Uncompressed, G3 (MH), G4 (MR/MMR)	MX-SCX1	Staple Cartridge (5,000 staples) (requires MX-FNX9/FN10)
	Photo, Map, Pale-Color Document. Settings: Auto or 9 step manual	Compression	Color/Grayscale: JPEG (high, middle, low)	AR-SC2	Staple Cartridge (5,000 staples) (requires MX-FN11/18)
Halftone	256 gradations/2 levels (monochrome)	Compression	Internet Fax mode: MH/MMR (option)	AR-SC3	Staple Cartridge (2,000 staples) (requires MX-FN10/18)
Copy Features	Scan-Once Print-Many, electronic sorting, offset-stacking, Auto Color	Scan Destinations	E-mail, Desktop, FTP, Folder (SMB), USB, Internet fax (option),	MX-TRX2	Right Exit Tray
	Sensing (ACS), Auto Paper Sensing (APS), Auto Magnification Sensing		Super G3 fax (option)	MX-TU13	Center Exit Tray
	(AMS), image preview, image edit, auto tray switching, rotation copy,	One-touch Dest.	Up to 2000 (combined scan destinations)	MX-PUX1	XPS Expansion Kit (Requires MX-SHP1GBCR3)
	reserve copy, tandem copy, book copy, margin shift, tab-paper	Group Destinations	•	MX-SHP1GBCR3	1GB Memory Upgrade (Required for MX-PUX1)
	insertion, edge erase, center erase, book divide, dual page copy, cover	Programs	48 (combined)	MX-FX11	Fax Expansion Kit
	pages, insert pages, OHP insertion, job build, card shot, blank page	Max. Jobs	Up to 100	MX-FWX1	Internet Fax Kit
	skip, mirror image, black-white reversal, centering, proof copy, 2-in- 1/4-in-1/8-in-1, pamphlet, watermark custom image, job programs.	NETWORK Protocols	TCP/IP and SSL (includes HTTP, SMTP, LDAP, FTP, POP3), SMB, ESMTP and 802.1x.	MX-PF10 AR-SU1	Bar Code Font Kit Stamp Unit (Requires AR-SV1 Stamp Cartridge)
Account Control	Up to 1000 users. Supports user-number authentication (on device),	Network Security	E-mail server user authentication for LDAP and Active Directory	AR-SV1	Stamp Unit (Requires AK-SVT Stamp Cartridge) Stamp Cartridge
Account control	login name/password (on device) or login name/password (on device)	Software	Sharpdesk® desktop pesonal document management software	MX-KB11	Keyboard (Standard on the MX-4111N/5111N)
	via LDAP server) for Copy, Print, Scan, Fax and document management.	50	(1 user license included)	MX-EB11	Enhanced Compression Kit
Output Tray	Main output tray (top) 400 sheets (face down); optional eject			MX-EB12	Mirror Expansion Kit
	tray (right 1 side) 100 sheets (face down)	B&W Super G3 Fa	x Kit (option)	MX-AMX1	Application Integration Module
Firmware	Flash ROM with local (USB), network update capability and firmware	Transmission	Super G3, G3	MX-AMX2	Application Communication Module (standard on MX-5111N)
	update 1 to N with SRDM (Sharp Remote Device Management)	Modem Speed	33.6 KBPS ³	MX-AMX3	External Accounting Module
	Web-based management with user/administrator level login, cloning	Compression	JBIG, MMR, MR, MH	MX-FR33U	Commercial Data Security Kit (not available at time of launch)
	(1 to N) with SRDM and remote front panel access	Scanning Method	Sheet fed simplex or duplex or book	MX-EC50	CAC Reader (Requires Data Security Kit)
	Remote front panel, remote access to service logs and click counts	Max. Resolution	400 dpi	DVENDPS	Generic Vendor Interface Kit
Accessibility	Tilt Front Panel, Adjustment of Key Touch-Send and Speed, Concave Key, Document Feeder Free Stop, Job Programs, Remote Front Panel,	Transmit Speed Auto Dialing	Approx. 2 seconds with Super G3/JBIG ⁴ Up to 2000 (combined scan destinations)	Supplies	
			Up to 500 destinations		Black Toner Cartridge
	Universal Grip for Paper Trays, and Disable Screen Timeout International Energy Star Program Ver. 1.1, Law on Promoting Green	Group Dial Inbound Fax	Routing: Forwards received fax data to E-mail	MX-51NTBA MX-51NTCA	Cyan Toner Cartridge
	Purchasing. European RoHS (Restriction of Hazardous Substances)	Long Length	Up to 31½" (for transmission)	MX-51NTMA	Magenta Toner Cartridge
	AC 100-127 VAC, 60 HZ, 16 Amps	Originals		MX-51NTYA	Yellow Toner Cartridge
	Maximum: 1440 W or less	Programs	48 (combined)	MX-51NVBA	Black Developer
Weight	MX-4110N/4111N: Approx. 276.5 lbs./MX-5110N/5111N: 278 lbs.	Memory	Shared	MX-51NVSA	Cyan/Magenta/Yellow Developer
	25½" (w) x 30" (d) x 38" (h)	Halftone	256 levels	MX-31NRSA	Drum















SHARP ELECTRONICS CORPORATION Sharp Plaza, Mahwah, NJ 07495-1163 1-800-BE-SHARP • www.sharpusa.com Design and specifications subject to change without notice. Sharp, Sharp OSA, Sharpdesk, My Sharp, and all related trademarks are trademarks or registered trademarks of Sharp Corporation and/or its affiliated companies. Windows, Windows NT, Windows Server and Windows Vista are trademarks or registered trademarks of Microsoft Corporation. All other trademarks are the property of their respective owners.

¹ Some features require optional equipment. See your local dealer.

² May vary depending on product configuration, machine settings

and operating and/or environmental conditions.

³ Actual transmission time will vary based on line conditions.

⁴ Based on Sharp Standard Test Chart with approximately 700 characters, letter size in standard resolution.